

SBC-06D2X-U

2011 iF Award Winning BDXL External Blu-ray Combo

Winner of 2011 iF design award, SBC-06D2X-U external Blu-ray combo provides extreme 6X Blu-ray reading speed and the latest BDXL format support. The attractive design has already won an iF Design Award for its innovation, versatility and aesthetics.















▶ FEATURES

The Best Data Back Up Solution

- ATP technology assure the best burning
- Disc Encryption II double the security
- \bullet Drag and Burn 3 steps to complete burning

The Most Extensive Compatibility

- BDXL format support
- Multiple OS support

Award Winning ID Design

- Vertical and Horizontal placement flexible and space saving
- Stylish design architecture-inspired design
- Award winning 2011 iF design award and 2012 Taiwan excellence award

▶SPECIFICATIONS

Read Speed	BD-R(SL/DL):6X BD-RE(SL/DL):6X BD-ROM(SL/DL):6X BD-R(TL/QL):4X BD-RE(TL):4X	DVD±R/±RW/ROM:8X DVD±R(DL):6X DVD-ROM(DL):6X DVD-RAM:5X CD-R/RW/ROM:24X	BDMV playback:2X DVD video playback:4X VCD playback:16X Audio CD Playback:10X
Write Speed	DVD±R:8X DVD+RW:8X DVD-RW:6X	DVD±R(DL):6X DVD-RAM:5X	CD-R:24X CD-RW:16X
Writing Mode	DVD+R; DVD+R DL: Sequential write DVD-R; DVD-R DL: DAO, Incremental Recording DVD+RW: Random Write DVD-RW: DAO, Incremental Recording, Restricted Overwrite DVD-RAM: Random Write CD-R/RW: DAO, TAO, SAO, Packet Write		
Access Time(1/3 Stroke)	BD: 230ms, DVD:180ms, CD:190ms		
Interface	USB 2.0		
OS Compatibility	Windows® 7, Windows® Vista, Windows® XP MAC OS X 10.6 or above		
System Requirement	Processor: Pentium® D 945(3.4GHz) or higher Memory: I GB or more is recommended Graphics Card: NVIDIA® GeForce 7600 GT or ATI X1600 series or above Use HDCP Compatible display and VGA card to High Definition digital output		
Disc Formats	• Reading: BD-R(SL/DL/TL/QL) BD-RE(SL/DL/TL) BD-ROM(SL/DL) DVD±R(SL/DL) DVD±RW DVD-ROM(SL/DL) DVD-RAM • Writing:	DVD Video CD-R CD-RW CD-ROM Audio CD VCD	CD-I CD-Extra Photo CD CD-text CD-ROM/XA Multi-session CD

DVD-RAM

CD-R

Configurations

Disc Diameters

Mounting Orientation	N/A
Dimensions	157 x 140 x 18.5 mm
	(L/W/H)
Weight	290g (335g with stand)

DVD±R(SL/DL)

12cm and 8cm

DVD±RW

Electrical and Environmental Specifications

CD-RW

Power Requirement	USB Power +5V ± 5%
Temperature	Operating: 5 ° C to 40 ° C Storage: -30 ° C to 60 ° C
Humidity	Operating:15%~80% (Non-condensing) Storage:10%~90% (Non-condensing)

Package Contents

- ASUS SBC-06D2X-U Drive
 A detachable stand
 Bundled software (Cyberlink Power2Go 7 / TurboEngine)
 ASUS Firmware update
 Quick installation guide







BDXL™ Format Support

Better Disc Compatibility

BDXL read only format allows user to read huge amount of data on a single Blu-ray disc, up to 100GB on BD-R(TL) and 128GB on BD-R(QL)





Superior Burning Solution

The Best Burning Quality

Auto Tuning Power Technology ensures optimized power to burn a disc with the best quality





Disc Encrytion II

Double Security On-the-Go

Password control access and hidden-file folder function





Drag-and-Burn

3 Easy Steps to Complete Disc Burning

Intuitive burning interface in only 3 simple steps to burn a disc





Aesthetics of Technology

Flexible Dual Positioning

Vertical and horizontal two-way placement



Architecture-inspired Design

Winner of 2011 iF Design Award, the product is designed based on a mini architecture concept, giving it precision-cut and elegant lines

